

Kinetrol Model 15 Spring Return Single Acting Actuator

Specification

Angle of Travel (adjustable)

80° - 100°

(restricted travel versions available)

Displaced Volume

5920 cm³ / 361 in³

Materials of Construction

Casing: Pressure die cast aluminium alloy

Vane & Output Shaft: SG iron, zinc plated

Shaft bushes: PTFE coated bronze (lead free)

Seals: Moulded polyurethane

Seal expanders: Stainless spring steel

Clock Type Spring: Carbon spring steel

Finish

Epoxy stove enamel

Weight

75.3 kg / 166.3 lb (excluding coupling)

Operating Temperature

-40°C to +80°C (-40°F to +176°F)



ATEX Category 2

Spring Torques

Metric Units - Nm

Actuator Model	Position of air OR spring return stroke	Pressure (bar)											
		1.7	2.0	2.4	2.8	3.1	3.5	3.8	4.1	4.5	4.8	5.2	5.5
15-120	Start						614.0	680.0	752.0	801.0	848.0	914.0	962.0
	Finish						392.0	392.0	522.0	590.0	656.0	723.0	790.0

English Units - lbf ins

Actuator Model	Position of air OR spring return stroke	Pressure (psi)											
		25	30	35	40	45	50	55	60	65	70	75	80
15-120	Start						5434	6018	6656	7089	7505	8090	8514
	Finish						3469	4098	4620	5222	5806	6399	6992

Options

- ISO Flange / Female drive spring option
- Low pressure spring option
- Limit switch boxes for open/closed indication - various switches including hazardous area
- Integral solenoid valve
- AP pneumatic positioner - full range of options
- EL electropneumatic positioner - full range of options
- P3 on/off positioner - full range of options including hazardous area
- Clear Cone monitor
- 180° and 120° model
- Spring to centre
- Geared manual override
- High temperature / Low temperature options
- VDI/VDE 3845 Namur accessory mounting option available - contact Kinetrol
- Available in BlueLine paint finish
- G3 Damper Drive

Kinetrol Model 15 Spring Return Single Acting Actuator

Product Code

● Air Ports

● Mount Holes

154-120 Metric Spring Return Clockwise	G½	4 x M16 x 28.5 deep on 140.0 PCD
154-130 Metric Spring Return Counter Clockwise	G½	4 x M16 x 28.5 deep on 140.0 PCD
157-120 English Spring Return Clockwise	½ NPT	4 x 5⁄8-11 UNC x 1.13" deep on 5.51" PCD
157-130 English Spring Return Counter Clockwise	½ NPT	4 x 5⁄8-11 UNC x 1.13" deep on 5.51" PCD

For female drive part codes contact Kinetrol

Visual red indicator supplied as standard

Dimensions

