

Kinetrol Model 18 Spring Unit

Specification

Spring Torque

Start 2954 Nm / 26143 lbf ins

Finish 2417 Nm / 21390 lbf ins

For actuated torques see single acting spring return actuator torque data sheets

For reduced spring torques contact Kinetrol

Angle of Travel

0° - 90°

Materials of Construction

Casing: Sand cast aluminium alloy

Output Shaft: Stainless steel

Clock Type Spring: Carbon spring steel

Finish

Epoxy stove enamel

Weight

184.0 kg / 405.6 lb

Operating Temperature

-40°C to +80°C (-40°F to +176°F)



Options

- ISO Flange / Female drive spring option
- Low pressure spring option
- High temperature / Low temperature options

Non Kinetrol Actuator Application Notes

Kinetrol spring units can be used in non Kinetrol actuator applications however the following must be considered.

A static gasket is provided to seal the base plate mounting face but the user's shaft must also be sealed to prevent water ingress into the spring housing.

External stops will need to be used to prevent the spring angle of travel from exceeding 90°.

See Kinetrol installation, operation and maintenance instructions for application example.

Kinetrol Model 18 Spring Unit

Product Code

184-020

Metric Spring Return Clockwise

184-030

Metric Spring Return Counter Clockwise

187-020

English Spring Return Clockwise

187-030

English Spring Return Counter Clockwise

Mount Holes

4 x M30 x 50 deep on 226.3 PCD

4 x M30 x 50 deep on 226.3 PCD

4 x 1 $\frac{1}{8}$ -7 UNC x 2.00" deep on 8.91" PCD

4 x 1 $\frac{1}{8}$ -7 UNC x 2.00" deep on 8.91" PCD

For female drive part codes contact Kinetrol

Dimensions

