

Kinetrol Model 05 Double Acting Actuator

Specification

Angle of Travel (adjustable)

74° - 100°

(restricted travel versions available)

Displaced Volume

113 cm³ / 6.9 in³

Materials of Construction

Casing: Pressure die cast aluminium alloy

Vane & Output Shaft: Stainless steel

Shaft bushes: PTFE coated bronze (lead free)

Seals: Moulded polyurethane

Seal expanders: Stainless spring steel

Finish

Epoxy stove enamel

Weight

0.78 kg / 1.72 lb (excluding coupling)

Operating Temperature

-40°C to +80°C (-40°F to +176°F)



ATEX Category 2

Double Acting Torques

Metric Units - Nm

Actuator Model	Pressure (bar)											
	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0
05-100	9.0	12.5	16.5	20.0	24.0	27.5	31.5	35.0	39.0	43.0	46.5	50.5

English Units - lbf ins

Actuator Model	Pressure (psi)									
	20	30	40	50	60	70	80	90	100	
05-100	70	116	160	205	250	300	346	393	440	

Options

- Fail safe spring return units
- clockwise or counter clockwise
- Limit switch boxes for open/closed indication
- various switches including hazardous area
- Integral solenoid valve
- AP pneumatic positioner - full range of options
- EL electropneumatic positioner - full range of options
- P3 on/off positioner - full range of options including hazardous area
- Clear Cone monitor
- 180° and 120° model
- Female drive and mounting details to DIN 3337 and ISO 5211
- ISO adaptor
- G¹/₄ or ¹/₄ NPT air port option available - contact Kinetrol
- Spring to centre
- Geared manual override
- High temperature / Low temperature options
- VDI/VDE 3845 Namur accessory mounting option available - contact Kinetrol
- Available in BlueLine paint finish

Kinetrol Model 05 Double Acting Actuator

Product Code

054-100

057-100

Air Ports

G $\frac{1}{8}$

$\frac{1}{8}$ NPT

Mount Holes

6 x M5 x 10 deep on 34.9 PCD
2 x M8 x 9 deep on 50.8 CTRS

6 x 10-24 UNC x 0.39" deep on 1.375" PCD
2 x $\frac{5}{16}$ -18 UNC x 0.35" deep on 2" CTRS

Visual red indicator supplied as standard

Dimensions

