

Kinetrol Standard Yellow Epoxy Paint Chemical Compatibility Chart

	RESISTANCE	
CHEMICAL	MEASURE:	
Inorganic chemicals		
Ammonium hydroxide (10%)	1	
Calcium chloride (50%)	1	
Caustic potash solution (10%)	1	
Sodium hypochorite (saturated)	1	
Caustic soda solution (10%)	1	
Caustic soda solution (saturated)	1	
Phosphoric acid (10%)	1	
Phosphoric acid (50%)	2	
Nitric acid (10%)	1	
Nitric acid (50%)	5	
Hydrochloric acid (10%)	2	
Hydrochloric acid (concentrated)	2	
Sulphuric acid (50%	1	
Sulphuric acid (concentrated)	5	
Sodium chloride solution (saturated)	1	
Hydrogen peroxide (100%)	1	
Water	1	

Resistance grading		
1 Resistant		
2 Slight colour change		
3 Loss of gloss/softened		
4 Loss of gloss/very soft		
5 Complete destruction of coating		
All tests were 24 hour chemical spot tests		
carried out at room temperature according to		
ASTM D1308-79.		

Organic chemicals		
Acetone	5	
Acetonitrile	2	
Benzene	1	
Benzyl alcohol	3	
N-Butanol	1	
N-Butyl acetate	1	
Citric acid (10%)	5	
Chlorobenzene	1	
Chloroforme	2	
O-Chlorophenol	3	
Cyclohexane	2	
Cyclohexanone	2	
1,2-Dichloroethane	2	
Diethyl ether	1	
Dioxane	2	
Glacial acetic acid	2	
Ethanol	1	
Ethyl acetate	2	
Ethylene glycol	1	
Glycerine	1	
Hexane	1	
Isooctane	1	
Isopropanol	1	
Lactic acid	2	
Methanol	1	
Methylene chloride	2	
Methyl ethyl ketone	2	

Issue	Signed	Date	Doc. No. TD205
В		16/11/21	Page 1 of 2



Kinetrol Standard Yellow Epoxy Paint Chemical Compatibility Chart

N.N-Dimethylformamide	5
N-Methylpyrrolidon	5
Oxalic acid	1
Petroleum ether	1
Phenol	3
Turpentine	1
1,1,1-Trichloroethane	1
Tetrachloromethane	1
Trichloroethylene	1
Toluene	1
Xylene	1

Resistance grading	
1 Resistant	
2 Slight colour change	
3 Loss of gloss/softened	
4 Loss of gloss/very soft	
5 Complete destruction of coating	
All tests were 24 hour chemical spot tests	
carried out at room temperature according to	
ASTM D1308-79.	

Fuels/lubricants		
Four-star petrol	1	
Fuel M 15	1	
Diesel Oil	1	
Kerosene	1	
Hypoid bevel gear oil Shell Spirax HD 90	1	
Transmission oil Shell Spirax MA 80	1	
Cutting fluid	1	
Automatic transmission fluid Shell Dextra 11D 20-137	1	
Engine oil, mineral, Mihag 1500-40	1	
Engine oil, synthetic, Mobil SHC 10 W-40	1	
Brake fluid Hydraulan DOT 4	2	
Roller bearing grease DIN 51 825	1	

Detergents		
Genkeene	1	
Glysantin (BASF)/water	1	
Suds	2	
Washing up liquids	1	
Household detergents	1	

Miscellaneous		
Linseed oil	1	
Milk	1	
Silicone oils	1	

Issue
Signed
Date
Image: Constraint of the second se