

Kinetrol Model 05 Modular Spring Unit

Specification

Spring Torque

Start 20.9 Nm / 185 lbf ins

Finish 17.5 Nm / 155 lbf ins

For actuated torques see single acting spring return actuator torque data sheets

For reduced spring torques contact Kinetrol

Angle of Travel

0° - 97°

Materials of Construction

Casing: Extruded and pressure die cast aluminium alloy

Output Shaft: Stainless steel

Clock Type Spring: Carbon spring steel

Finish

Epoxy thermoset powder

Weight

1.18 kg / 2.60 lb

Operating Temperature

-40°C to +80°C (-40°F to +176°F)



ATEX Category 2

Options

☐ ISO Flange / Female drive spring option

☐ ISO adaptor

☐ High temperature / Low temperature options

☐ Available in Blueline paint finish

Non Kinetrol Actuator Application Notes

Kinetrol spring units can be used in non Kinetrol actuator applications however the following must be considered.

A static gasket is provided to seal the base plate mounting face but the user's shaft must also be sealed to prevent water ingress into the spring housing.

External stops will need to be used to prevent the spring angle of travel from exceeding 90°.

See Kinetrol installation, operation and maintenance instructions for application example.

Kinetrol Model 05 Modular Spring Unit

Product Code

054-0C0

Metric Spring Return Clockwise

054-0A0

Metric Spring Return Counter Clockwise

057-0C0

English Spring Return Clockwise

057-0A0

English Spring Return Counter Clockwise

Mount Holes

6 x M5 x 10 deep on 34.9 PCD

6 x M5 x 10 deep on 34.9 PCD

6 x 10-24 UNC x 0.39" deep on 1.375" PCD

6 x 10-24 UNC x 0.39" deep on 1.375" PCD

For female drive part codes contact Kinetrol

Dimensions

